

To accompany plans dated .

Post Type	Anchor Bolts			Round Pedestal					CIDH Pile								
	Total	Dia (mm)	BC (mm)	Total Length (mm)	Dia (mm)	Reinforcing		Ноор		Pile	Pile	Reinforcing			Spiral		
						Total	Bar Size	BC (mm)	Bar Size	Pitch	Dia (mm)	Depth (m) **	Total	Bar Size	BC (mm)	Bar Size	Pitch
I-S	12	51	711	1270	1600	16	32	1381	16	89	1372	5.5	26	32	1143	16	89
∏-S	12	51	711	1270	1600	16	32	1381	16	89	1372	6	26	32	1143	16	89
⊞-S	12	51	787	1270	1600	16	32	1381	16	89	1372	7	26	32	1143	16	89
I ∑ -S	14	51	864	1270	1600	16	32	1381	16	89	1372	7	26	32	1143	16	89
∑ -S	16	64	965	1524	1753	16	36	1533	16	89	1524	8	28	36	1295	16	89
∑ I−S	16	64	1041	1524	1753	16	36	1533	16	89	1524	8.5	28	36	1295	16	89
VII-S	16	64	1041	1524	1753	16	36	1533	16	89	1524	8.5	28	36	1295	16	89

* * Use Foundation Depth shown in table unless otherwise shown on the Project Plans.

Ν	0	Τ	Ε	S
- 1 7	v	-	ᆫ	J

- 1. For anchor bolt layout see post sheet.
- 2. For "Base P elevation" see Project Plans.
- 3. Longer side of post shall be normal to axis of sign.
- 4. Prior to erection of the post, backfill which is equivalent to the surrounding material, shall be in place.
- Pedestal shall be formed 150 mm Min below ground surface. Remainder to be placed against undisturbed material.
- 6. Slope protection required when indicated on the Project Plans.
- 7. Foundation design is based on 2001 AASHTO article 13.6 Broms' approximate procedure assuming a cohesionless material. The angle of internal friction used is 30° and unit weight of soil used is 1922 kg/m³.

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION

OVERHEAD SIGNS-TRUSS TWO POST TYPE ROUND PEDESTAL PILE FOUNDATION

NO SCALE

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN

RSP S15 DATED JANUARY 24, 2005 SUPERSEDES STANDARD PLAN S15 DATED JULY 1, 2004-PAGE 324 OF THE STANDARD PLANS BOOK DATED JULY 2004.

REVISED STANDARD PLAN RSP S15

75 CIr				
SECTION B-B				
Ground surface away from traffic for 51 mm Dia bolt for 64 mm Dia bolt Ground surface adjacent to traffic	Post Type I-S	Total	Dia (mm)	ı
E CO B STANDARD B 25 Min 155 Max	П-S П-S ГУ-S ГУ-S ГУ-S	12 12 14 16 16	51 51 51 64 64	3 2 3
Conduit, see lighting plan See "Anchorage Details" on Revised Std Plan RSP S9 and see Revised Std Plan RSP S10 #16 @ 89 #16 @ 89 Pedestal vertical reinforcement, see table for size Place concrete against undisturbed material Permissible Const joint		16 Use Footherv		
Vert Reinf Slope processed for the second surface adjacent to traffic adjacent to tra	11	offic-		
Vertical reinforcement equally spaced (See table) SECTION A-A	2	5 Min		

Pedestal Vert Reinf Total 16, see table for size

Spiral reinforcement

Axis of sign

Spiral #16 @ 89 pitch

Vertical reinforcement

Embed 1016 mm for 5 Embed 1270 mm for 6

2